

Arborist 150D MAX

SPECIFICATIONS

ENGINE	
BRAND	KUBOTA
(HP)	26HP/34HP
TYPE/MODEL	D1105
OIL (TYPE)	SAE15W-40
OIL (CAPACITY LITRES)	3.7
COOLING	WATER COOLED
CYLINDERS	3
FUEL / HYDRAULICS	
FUEL TYPE	DIESEL
FUEL CAPACITY	27L
HYDRAULIC OIL (TYPE)	ISO32-ISO46
HYDRAULIC OIL (CAPACITY)	30L
FEED ROLLER PUMP PRESSURE	3000PSI
TRACK PUMP PRESSURE	N/A
MACHINE	
CAPACITY	150MM
TONNES PER HOUR	3.75
LENGTH (TRANSPORT)	3556MM
WIDTH (TRANSPORT)	1290MM
HEIGHT	2335MM
WEIGHT	748KG
SOUND POWER (LWA)	115DB(A)
SOUND PRESSURE (PPA)	92DB(A)
INFEED CHUTE APERTURE (W X H)	970MM X 790MM
INFEED THROAT APERTURE (W X H)	150MM X 230MM
DISCHARGE CHUTE	ROTATION OF 280° ADJUSTABLE END CAP & SLIDE BAR
POWER FEED ROLLERS	2
ROLLER CONTROL BUTTONS	2 BANKS OF 2 (FORWARD REVERSE)
THROTTLE CONTROL	MANUAL
HYDRAULIC FLOW CONTROL VALVE	OPTIONAL
MAIN DRIVE BELT TENSIONING	AUTOMATIC
GREASING	EASILY ACCESSIBLE
FLYWHEEL / CHAMBER	
CHIPPING FLYWHEEL (TYPE)	DISC-BLADE
FLYWHEEL WEIGHT	47KG
BLADE (QTY)	4
FLYWHEEL SPEED	1700RPM
BOLT TORQUE	200 NM
SHEAR BAR TO BLADES GAP	2MM
AXLE / DRAWBAR	
ALKO	FULLY BRAKED SYSTEM OVER-RUN BRAKE HAND BRAKE
ADJUSTABLE A FRAME DESIGN	50MM BALL COUPLING AS STANDARD
ELECTRIC CABLE	REMOVABLE SPIRAL 13 PIN CABLE
SAFETY	
SAFETY BARS	EN 13525 COMPLIANT FLOATING BARS
TOP SAFETY BUTTON	EN 13525 COMPLIANT LOCATED ON INFEED CHUTE