

ChipMaster 220 TMP

SPECIFICATIONS

FUEL / HYDRAULICS

FUEL TYPE	PTO
RECOMMENDED TRACTOR POWER	60 - 80 HP

MACHINE

CAPACITY	220MM
TONNES PER HOUR	7
LENGTH (TRANSPORT)	2200MM
WIDTH (TRANSPORT)	1340MM
HEIGHT	2450MM
WEIGHT	950kg
SOUND POWER (LWA)	117dB(A)
SOUND PRESSURE (PPA)	92dB(A)
INFEED CHUTE APERTURE (W X H)	1100MM X 800MM
INFEED THROAT APERTURE (W X H)	230MM X 230MM
DISCHARGE CHUTE	ADJUSTABLE END CAP
THROTTLE CONTROL	MANUAL
GREASING	EASILY ACCESSIBLE

FLYWHEEL / CHAMBER

CHIPPING FLYWHEEL (TYPE)	DISC
FLYWHEEL WEIGHT	135KG
BLADE (QTY)	6
FLYWHEEL SPEED	1565 RPM
BOLT TORQUE	200 NM
SHEAR BAR TO BLADE GAP	2MM

SAFETY

TOP SAFETY BUTTON	EN 13525 COMPLIANT
SAFETY BARS	EN 13525 COMPLIANT FLOATING BARS