

SPECIFICATIONS

ENGINE

| | |
|-----------------------|------------------------|
| BRAND | LONCIN |
| (HP) | 24HP |
| TYPE/MODEL | LC2V80FD / 24HP (18KW) |
| OIL (TYPE) | SAE 10W-30 |
| OIL (CAPACITY LITRES) | 1.8L |
| COOLING | AIR |
| CYLINDERS | 2 |

FUEL / HYDRAULICS

| | |
|---------------------------|-------------|
| FUEL TYPE | PETROL |
| FUEL CAPACITY | 33L |
| HYDRAULIC OIL (TYPE) | ISO32-ISO46 |
| HYDRAULIC OIL (CAPACITY) | 33L |
| FEED ROLLER PUMP PRESSURE | 3000PSI |
| TRACK PUMP PRESSURE | N/AI |

MACHINE

| | |
|--------------------------------|---------------------------------------|
| CAPACITY | 135MM |
| TONNES PER HOUR | 4 |
| LENGTH (TRANSPORT) | 3200MM |
| WIDTH (TRANSPORT) | 1600MM |
| HEIGHT | 2300MM |
| WEIGHT | 640KGS |
| SOUND POWER (LWA) | 115DB(A) |
| SOUND PRESSURE (PPA) | 92DB(A) |
| INFEED CHUTE APERTURE (W X H) | 850MM X 680MM |
| INFEED THROAT APERTURE (W X H) | 150MM X 135MM |
| DISCHARGE CHUTE | ROTATION OF 280° ADJUSTABLE END CAP |
| POWER FEED ROLLERS | 2 |
| ROLLER CONTROL BUTTONS | 2 BANKS OF 2 (FORWARD REVERSE) |
| THROTTLE CONTROL | MANUAL |
| HYDRAULIC FLOW CONTROL VALVE | OPTIONAL |
| MAIN DRIVE BELT TENSIONING | AUTOMATIC |
| GREASING | EASILY ACCESSIBLE |

FLYWHEEL / CHAMBER

| | |
|--------------------------|------------|
| CHIPPING FLYWHEEL (TYPE) | DISC-BLADE |
| FLYWHEEL WEIGHT | 48KG |
| BLADE (QTY) | 2 |
| FLYWHEEL SPEED | 2500RPM |
| BOLT TORQUE | 200 NM |
| SHEAR BAR TO BLADES GAP | 2MM |

AXLE / DRAWBAR

| | |
|---------------------------|---|
| ALKO | FULLY BRAKED SYSTEM OVER-RUN BRAKE HAND BRAKE |
| ADJUSTABLE A FRAME DESIGN | 50MM BALL COUPLING AS STANDARD |
| ELECTRIC CABLE | REMOVABLE SPIRAL 13 PIN CABLE |

SAFETY

| | |
|-------------------|--|
| SAFETY BARS | EN 13525 COMPLIANT FLOATING BARS |
| TOP SAFETY BUTTON | EN 13525 COMPLIANT LOCATED ON INFEED CHUTE |