

ECO 150 TMP

SPECIFICATIONS

FUEL / HYDRAULICS

FUEL TYPE	PTO
RECOMMENDED TRACTOR POWER	25 - 45 HP

MACHINE

CAPACITY	150MM
TONNES PER HOUR	4.5
LENGTH (TRANSPORT)	1060MM
WIDTH (TRANSPORT)	1745MM
HEIGHT	2220MM
WEIGHT	490kg
SOUND POWER (LWA)	117dB(A)
SOUND PRESSURE (PPA)	93dB(A)
INFEED CHUTE APERTURE (W X H)	800MM X 700MM
INFEED THROAT APERTURE (W X H)	150MM X 150MM
DISCHARGE CHUTE	ADJUSTABLE END CAP
THROTTLE CONTROL	MANUAL
GREASING	EASILY ACCESSIBLE

FLYWHEEL / CHAMBER

CHIPPING FLYWHEEL (TYPE)	DISC
FLYWHEEL WEIGHT	47KG
BLADE (QTY)	2
FLYWHEEL SPEED	2400 RPM
BOLT TORQUE	200 NM
SHEAR BAR TO BLADE GAP	2MM

SAFETY

TOP SAFETY BUTTON	EN 13525 COMPLIANT
SAFETY BARS	EN 13525 COMPLIANT FLOATING BARS