

## SPECIFICATIONS

## ENGINE

BRAND	KUBOTA
(HP)	50HP
TYPE/MODEL	D1803-CR
OIL (TYPE)	SAE15W-40
OIL (CAPACITY LITRES)	6.5
COOLING	WATER COOLED
CYLINDERS	3

## FUEL / HYDRAULICS

FUEL TYPE	DIESEL
FUEL CAPACITY	50L
HYDRAULIC OIL (TYPE)	ISO32-ISO46
HYDRAULIC OIL (CAPACITY)	50L
FEED ROLLER PUMP PRESSURE	3000PSI
TRACK PUMP PRESSURE	2800PSI

## MACHINE

CAPACITY	205MM
TONNES PER HOUR	7
LENGTH (TRANSPORT)	3000MM (3770MM PLATFORM & FLAP DOWN)
WIDTH (TRANSPORT)	1450MM
HEIGHT	2730MM
WEIGHT	1700 KG
SOUND POWER (LWA)	118DB(A)
SOUND PRESSURE (PPA)	91DB(A)
INFEED CHUTE APERTURE (W X H)	1250MM X 700MM
INFEED THROAT APERTURE (W X H)	205MM X 270MM
DISCHARGE CHUTE	ROTATION OF 280°   ADJUSTABLE END CAP & SLIDE BAR
POWER FEED ROLLERS	2
ROLLER CONTROL BUTTONS	2 BANKS OF 3 ( FORWARD   REVERSE   THROTTLE
THROTTLE CONTROL	ELECTRIC
HYDRAULIC FLOW CONTROL VALVE	YES
MAIN DRIVE BELT TENSIONING	SELF TENSION BELTS / DE-CLUTCH WITH LEVER
GREASING	REMOTE   EASILY ACCESSIBLE
GROUND CLEARANCE	260MM
TRACK SPEED	3KPH

## FLYWHEEL / CHAMBER

CHIPPING FLYWHEEL (TYPE)	DISC-BLADE
FLYWHEEL WEIGHT	128KG
BLADE (QTY)	6
FLYWHEEL SPEED	1450RPM
BOLT TORQUE	200 NM
SHEAR BAR TO BLADES GAP	2.5mm

## OPTIONAL EQUIPMENT

BALL HITCH	BALL HITCH MOUNTED TO PLATFORM 750KG MAX
WINCH	3 TONNE FACTORY FIT ONLY
VARI-HEIGHT DISCHARGE CHUTE	YES

## SAFETY

SAFETY BARS	EN 13525 COMPLIANT FLOATING BARS
TOP SAFETY BUTTON	EN 13525 COMPLIANT   LOCATED ON INFEED CHUTE