

QuadTrak 160D

SPECIFICATIONS

ENGINE

BRAND	KUBOTA
(HP)	34HP
TYPE/MODEL	D1105T
OIL (TYPE)	SAE15W-40
OIL (CAPACITY LITRES)	3.7
COOLING	WATER COOLED
CYLINDERS	3

FUEL / HYDRAULICS

FUEL TYPE	DIESEL
FUEL CAPACITY	25L
HYDRAULIC OIL (TYPE)	ISO32-ISO46
HYDRAULIC OIL (CAPACITY)	23L
FEED ROLLER PUMP PRESSURE	1800PSI
TRACK PUMP PRESSURE	2500PSI

MACHINE

CAPACITY	160MM
TONNES PER HOUR	3.5
LENGTH (TRANSPORT)	2368MM
WIDTH (TRANSPORT)	1366MM
HEIGHT	2487MM
WEIGHT	1100KG
SOUND POWER (LWA)	116DB(A)
SOUND PRESSURE (PPA)	92DB(A)
INFEED CHUTE APERTURE (W X H)	1100MM X 800MM
INFEED THROAT APERTURE (W X H)	160MM X 230MM
DISCHARGE CHUTE	ADJUSTABLE END CAP
POWER FEED ROLLERS	2 VERTICAL
THROTTLE CONTROL	MANUAL
HYDRAULIC FLOW CONTROL VALVE	OPTIONAL
GREASING	EASILY ACCESSIBLE
TRACK SPEED	3KPH
GROUND CLEARANCE	240MM

FLYWHEEL / CHAMBER

CHIPPING FLYWHEEL (TYPE)	DISC BLADE
FLYWHEEL WEIGHT	47KG
BLADE (QTY)	4
FLYWHEEL SPEED	2200RPM
BOLT TORQUE	200 NM
SHEAR BAR TO BLADES GAP	2MM

AXLE / DRAWBAR

ALKO	FULLY BRAKED SYSTEM OVER-RUN BRAKE HAND BRAKE
ADJUSTABLE A FRAME DESIGN	50MM BALL COUPLING AS STANDARD
ELECTRIC CABLE	REMOVABLE SPIRAL 13 PIN CABLE

SAFETY

SAFETY BARS	EN 13525 COMPLIANT FLOATING BARS
TOP SAFETY BUTTON	EN 13525 COMPLIANT LOCATED ON INFEED CHUTE