

Model: ChipMaster 220 TMP

| | Description | Notes |
|----------------------------|---|--|
| Basics | Weight | 860Kgs |
| | Max Timber Diameter | 220mm |
| | Throughput | 7 tonnes per hour |
| | Hydraulic Oil Tank Capacity | 44 Litres - Fitted with sight gauge and filter. |
| Engine | Tractor Mounted | 60 - 80 hp |
| | Clutch | N/A |
| Chipping | Power Feed Rollers | 2 |
| | | Hydraulically driven by two motors one on each |
| | Disc Processor/ Flywheel | 48Kgs |
| | Disc Blade Cutters | 6 cutters. |
| | | 720-900 Hours expected life on clean material. |
| | Flywheel Speed | 1565 rpm |
| | Main Drive Shaft Bearings | Oversized, Greaseable. |
| | Infeed Chute Aperture (W X H) | 1000mm x 800mm |
| | Infeed Throat Aperture (W x H) | 230mm x 230mm |
| Sound Pressure LPA | 92 dB(A) | |
| Sound Power LWA | 117 dB(A) | |
| Controls | Throttle Control | Manual Lever type. |
| | No Stress | Yes |
| Safety | Safety Bars | EN 13525 Compliant |
| | | Floating to equalize pressure at all points. |
| | | Built in sections to remove cost of replacement. |
| Discharge | Discharge Chute | Rotation of 280° to safeguard the operator. |
| | | Adjustable end cap to direct material. |
| Dimensions: | Length Transport | 2200mm |
| | Width Transport | 1340mm |
| | Height with Discharge Chute Up | 2450mm |
| | Dimensions can be reduced for LCL and FCL Ocean Freight, please ask for details. | |
| Optional Equipment: | Corporate Colour Choice | Standard RAL Colours only. |